

UniPACK-P/UniPACK -P EXP R290 High Temperature Air Source Heat Pump



Available for new installations and renovations

Design, Supply and Commissioning
packages available

UniPACK-P EXP

TXAEP 251÷4160

Cooling capacity 47÷158,8 kW
Heating capacity 49,1÷161,1 kW



Features

Efficient and eco-friendly range in R290

Temperature of the produced water up to 72°C

TER up to 7,74

Extended operating limits

Integrated MASTER/SLAVE control

Tax incentives*



**EXPsystems – Air cooled multi-purpose ecological system with axial fans.
Range with scroll hermetic compressors and R290 refrigerant gas.**

Construction features

- Compressor: hermetic rotary, scroll type, complete with thermal protection and casing heater.
- 2-4 capacity steps with high efficiency at part loads.
- Main and secondary heat exchangers: crossed flow stainless steel plate exchangers, complete with antifreeze heater, closed cell polyurethane foam rubber insulation and water flow differential pressure switch.
- Air side heat exchanger: finned coil with copper pipes and aluminium fins.
- Fan: external rotor axial type electric fans equipped with internal thermal protection and accident protection grilles. The electric fans, based on the sizes, are EC fans or fitted with a proportional electronic device for continuous adjustment of the rotation speed.
- Control: microprocessor electronic control with Adaptive Function Plus logic.
- Structure: made of galvanised and painted steel plate with polyester powder coating.
- Refrigerant leak detector.
- Coil protection nets.

- The unit is also complete with:
 - compressor and fan circuit breaker switches;
 - electronic expansion valve;
 - display of cooling circuit high/low pressure;
 - master/slave control up to 4 units in parallel;
 - clock board;
 - control of Variable Primary Flow (VPF_R).

Versions

- T - High efficiency version.
- Q - Super silenced version complete with compressor technical compartment soundproofing and reduced speed fans.

Models

- TXAETP: EXPsystems unit.
- TXAEQP: super silenced EXPsystems unit.

Factory fitted accessories

- PUMP with single or double electric pump, one of which automatic in standby. The electric pumps are available in the low or high head versions.
- Inverter pump control for unit start-up.
- Recovery side VPF_R control.
- Desuperheater.
- Condensing control with fans with EC motor (standard in sizes 251-280).
- Condensing control with over-pressure fans (T version only)
- Power factor correction capacitors ($\cos\phi > 0.94$).
- Forced limit of power consumption.
- Forced noise limit.
- Energy parameter measuring device.
- Soft starter.
- Compressor technical compartment soundproofing.
- Compressor soundproof enclosures.
- Double safety valves.
- Buffer panels.
- Copper/copper, pre-painted copper/aluminium or with hydrophilic treatment coils.
- Control of min/max power supply voltage and backup battery.
- Digital input for double set-point.
- 4-20 mA analogue signal for shifting set-point.
- Contacts for Smart Grid integration and photovoltaic system.
- Electrical panel resistance, base, electric pumps and heat exchangers for heat recovery, if any.
- Interfaces for serial communication with other devices.
- Colour touch user keypad (fitted on the machine or remotely) with 7" display.
- Anti-vibration mounts.

Separately supplied accessories

- Remote keypad with display.
- Thermostat with display.
- Rhoss supervisors for unit monitoring and remote management.
- Rhoss sequencer for integrated management of multiple chillers.

Technical data

TXAETP MODEL		251	260	270	280	4100	4110	4120	4130
COOLING OPERATIONS (AUTOMATIC 1 MODE)									
① Nominal cooling capacity	kW	48,5	58,4	68,4	79,4	95,9	104,9	117,9	126,9
① Absorbed power	kW	16,3	19,8	22,9	26,7	32,7	36,3	40,9	43
① E.E.R.		2,98	2,95	2,99	2,97	2,93	2,89	2,88	2,95
COOLING OPERATIONS + TOTAL RECOVERY (AUTOMATIC 2 MODE)									
② Nominal cooling capacity	kW	48,9	59,2	69,7	81	97,9	107	120,9	128,7
② Recovery heating capacity	kW	63,2	76,3	90,3	104,4	126,5	138,5	155,7	166,6
② T.E.R.		7,57	7,67	7,5	7,67	7,57	7,52	7,7	7,53
HEATING OPERATIONS (MODE SELECT 1-2 AUTOMATIC 3)									
② Nominal heating capacity	kW	50,1	59,1	71,1	80,1	102,1	110,1	120,1	134,1
② Absorbed power	kW	15,6	18,3	21,8	24,5	31,8	34,4	37,4	41,8
② C.O.P.		3,21	3,23	3,26	3,27	3,21	3,2	3,21	3,21
TXAEQP MODEL									
COOLING OPERATIONS (AUTOMATIC 1 MODE)									
① Nominal cooling capacity	kW	47	56,4	66,4	76,9	92,9	101,9	112,9	123,9
① Absorbed power	kW	16,4	19,9	23	26,9	33,5	37,2	42,1	43,6
① E.E.R.		2,87	2,83	2,89	2,86	2,77	2,74	2,68	2,84
COOLING OPERATIONS + TOTAL RECOVERY (AUTOMATIC 2 MODE)									
② Nominal cooling capacity	kW	49,1	59,4	69,9	81,3	98,2	107,3	121,4	129
② Recovery heating capacity	kW	63,4	76,4	90,5	104,7	126,8	138,8	156,1	166,9
② T.E.R.		7,61	7,7	7,52	7,7	7,6	7,55	7,74	7,55
HEATING OPERATIONS (MODE SELECT 1-2 AUTOMATIC 3)									
② Nominal heating capacity	kW	49	58,1	70,1	79,1	100,1	108,1	118,1	132,1
② Absorbed power	kW	15,1	17,7	21	23,8	31,2	33,8	36,8	41
② C.O.P.		3,25	3,28	3,34	3,33	3,21	3,2	3,21	3,22
TXAETP-TXAEQP MODEL									
① TXAETP sound pressure	dB(A)	49	49	51	52	53	53	54	55
① TXAEQP sound pressure	dB(A)	44	45	46	47	48	48	49	50
② TXAETP sound power	dB(A)	81	81	83	84	85	85	86	87
② TXAEQP sound power	dB(A)	76	76	78	79	80	80	81	82
Scroll compressors/steps	no.	2/2	2/2	2/2	2/2	4/4	4/4	4/4	4/4
Circuits	no.	2	2	2	2	2	2	2	2
Electrical supply	V-ph-Hz	400-3+N-50	400-3+N-50	400-3+N-50	400-3+N-50	400-3-50	400-3-50	400-3-50	400-3-50
DIMENSIONS AND WEIGHTS									
L – Width	mm	2550	2550	3250	3250	3250	3250	3250	3930
H – Height	mm	2210	2210	2210	2210	2260	2260	2260	2260
P – Depth	mm	1570	1570	1570	1570	1970	1970	1970	1970
③ TXAETP weight	kg	1335	1345	1600	1625	2000	2005	2040	2305
③ TXAEQP weight	kg	1390	1400	1685	1710	2075	2080	2115	2385
SEASONAL ENERGY PERFORMANCE									
TXAETP MODEL SEASONAL ENERGY PERFORMANCE IN HEATING MODE – Low temperature application 35°C									
① Pdesignh (EN 14825)	kW	41	48	58	65	83	90	98	109
① SCOP (EN 14825)		3,74	3,7	3,73	3,73	3,8	3,77	3,75	3,78
② ηs	%	147	145	146	146	149	148	147	148
② Energy class		A+	A+	A+	A+	-	-	-	-
TXAEQP MODEL SEASONAL ENERGY PERFORMANCE IN HEATING MODE – Low temperature application 35°C									
① Pdesignh (EN 14825)	kW	40	47	57	64	82	88	96	108
① SCOP (EN 14825)		3,73	3,71	3,77	3,76	3,73	3,74	3,71	3,71
② ηs	%	146	145	148	147	146	147	146	145
② Energy class		A+	A+	A+	A+	-	-	-	-
TXAETP MODEL SEASONAL PERFORMANCE IN HEATING MODE – Medium temperature application 55°C									
① Pdesignh (EN 14825)	kW	40	47	56	63	82	88	96	106

① SCOP (EN 14825)		3,15	3,11	3,12	3,14	3,22	3,19	3,16	3,23
② ηs	%	123	121	122	123	126	125	123	126
② Energy class		A+	A+	A+	A+	-	-	-	-
TXAEQP MODEL SEASONAL PERFORMANCE IN HEATING MODE – Medium temperature application 55°C									
① Pdesignh (EN 14825)	kW	39	46	55	62	81	87	95	105
① SCOP (EN 14825)		3,15	3,11	3,15	3,17	3,17	3,15	3,12	3,16
② ηs	%	123	122	123	124	124	123	122	124
② Energy class		A+	A+	A+	A+	-	-	-	-
TXAETP MODEL						4140	4150	4160	
COOLING OPERATIONS (AUTOMATIC 1 MODE)									
① Nominal cooling capacity					kW	135,9	147,9	158,8	
① Absorbed power					kW	46,4	51	54,4	
① E.E.R.						2,93	2,9	2,92	
COOLING OPERATIONS + TOTAL RECOVERY (AUTOMATIC 2 MODE)									
② Nominal cooling capacity					kW	137,8	150,6	162,1	
② Recovery heating capacity					kW	178,6	194,8	208,9	
② T.E.R.						7,49	7,56	7,67	
HEATING OPERATIONS (MODE SELECT 1-2 AUTOMATIC 3)									
② Nominal heating capacity					kW	143,2	153,1	161,1	
② Absorbed power					kW	44,6	47,7	50,2	
② C.O.P.						3,21	3,21	3,21	
TXAEQP MODEL						4140	4150	4160	
COOLING OPERATIONS (AUTOMATIC 1 MODE)									
① Nominal cooling capacity					kW	131,9	143,9	152,9	
① Absorbed power					kW	47,1	51,9	55,8	
① E.E.R.						2,8	2,77	2,74	
COOLING OPERATIONS + TOTAL RECOVERY (AUTOMATIC 2 MODE)									
② Nominal cooling capacity					kW	138,2	151,1	162,7	
② Recovery heating capacity					kW	178,9	195,2	209,5	
② T.E.R.						7,52	7,6	7,7	
HEATING OPERATIONS (MODE SELECT 1-2 AUTOMATIC 3)									
② Nominal heating capacity					kW	140,1	149,1	158,1	
② Absorbed power					kW	43,5	46,6	49,3	
② C.O.P.						3,22	3,2	3,21	
TXAETP-TXAEQP MODEL						4140	4150	4160	
④ TXAETP sound pressure					dB(A)	55	55	56	
④ TXAEQP sound pressure					dB(A)	50	50	51	
⑥ TXAETP sound power					dB(A)	87	87	88	
⑥ TXAEQP sound power					dB(A)	82	82	83	
Scroll compressors/steps					no.	4/4	4/4	4/4	
Circuits					no.	2	2	2	
Electrical supply					V-ph-Hz	400-3-50	400-3-50	400-3-50	
DIMENSIONS AND WEIGHTS						4140	4150	4160	
L – Width					mm	3930	3930	3930	
H – Height					mm	2260	2260	2260	
P – Depth					mm	1970	1970	1970	
④ TXAETP weight					kg	2310	2360	2365	
④ TXAEQP weight					kg	2390	2440	2445	
SEASONAL ENERGY PERFORMANCE						4140	4150	4160	
TXAETP MODEL SEASONAL ENERGY PERFORMANCE IN HEATING MODE – Low temperature application 35°C									
① Pdesignh (EN 14825)					kW	116	124	131	
① SCOP (EN 14825)						3,75	3,74	3,72	
② ηs					%	147	147	146	
② Energy class						-	-	-	
TXAEQP MODEL SEASONAL ENERGY PERFORMANCE IN HEATING MODE – Low temperature application 35°C									
① Pdesignh (EN 14825)					kW	114	121	128	
① SCOP (EN 14825)						3,7	3,69	3,68	
② ηs					%	145	144	144	
② Energy class						-	-	-	

TXAETP MODEL SEASONAL PERFORMANCE IN HEATING MODE – Medium temperature application 55°C				
① Pdesignh (EN 14825)	kW	113	120	127
① SCOP (EN 14825)		3,2	3,18	3,18
② ηs	%	125	124	124
② Energy class		-	-	-
TXAEQP MODEL SEASONAL PERFORMANCE IN HEATING MODE – Medium temperature application 55°C				
① Pdesignh (EN 14825)	kW	111	118	125
① SCOP (EN 14825)		3,14	3,13	3,14
② ηs	%	123	122	122
② Energy class		-	-	-

Data at the following conditions:

- ① Air: 35°C – Water: 12/7°C.
 - ② Air: 7°C D.B. – 6°C W.B. – Water: 40/45°C.
 - ③ Evaporator output water: 7°C, nominal flow rate. Recovery output water: 45°C, nominal flow rate.
 - ④ In open field (Q = 2) at 10 m from the unit.
 - ⑤ Total sound power level in dB(A) based on measurements carried out in accordance with regulation UNI EN-ISO 9614.
 - ⑥ Weight referred to the unit without load and not accessorised.
- Performance according to EN 14511.
T.E.R.: Total efficiency ratio
- ① In Average climatic conditions
 - ② Seasonal energy efficiency: heating in Average climate (EU Regulations No.811/2013 and No.813/2013)

CONTACT US TODAY

HEAD OFFICE

Unit 19a
Scarva Road Industrial Estate
Banbridge, Co. Down, BT32 3QD

BELFAST OFFICE

10c Hydepark Road
Mallusk, Newtownabbey
BT36 4PY

REPUBLIC OF IRELAND OFFICE

IDA Finnabair Science &
Technology Park, Dundalk
Co.Louth, Ireland

GLASGOW OFFICE

Unit 6, Airlink Industrial Estate
Inchinnan Road
Paisley, PA3 2RS

BIRMINGHAM OFFICE

6100 Knights Court
Solihull Parkway
Birmingham Business Park
Solihull, B37 7WY



E: info@alternativeheat.co.uk

T: +44 (0) 28 437 70700

www.alternativeheat.co.uk

alternativeHEAT
Commercial Energy Solutions

